

Výpis podrobných a hlavních bodů

Niveleta: Profil - SO 102

Trasa: SO 102

Popis:

Rozsah staničení: Počáteční: 0.00, Koncové: 451.02

Krok staničení: 20.00

Bod	Staničení	Y	X	Z	Celková délka	Typ	Směrník:	Poloměr
1	0	724061,23	1028316,77	172,59	0	ZU, V	272 019	-
2	17,76	724077,3	1028324,32	172,54	17,76	TK	272 019	-
3	20	724079,31	1028325,3	172,53	20		270 235	80
4	23,74	724082,61	1028327,07	172,52	23,74		267 257	80
5	29,72	724087,7	1028330,2	172,5	29,72	KT	262 496	80
6	40	724096,25	1028335,91	172,47	40		262 496	-
7	52,88	724106,96	1028343,07	172,43	52,88	ZZ	262 496	-
8	60	724112,88	1028347,02	172,41	60		262 496	-
9	68,42	724119,88	1028351,7	172,4	68,42	Spád 0% (nejnižší)	262 496	-
10	73,84	724124,38	1028354,71	172,41	73,84	TK	262 496	-
11	77,73	724127,57	1028356,94	172,41	77,73		260 019	100
12	80	724129,4	1028358,29	172,42	80	V	258 573	100
13	81,62	724130,68	1028359,28	172,42	81,62	KT	257 543	100
14	99,25	724144,53	1028370,19	172,5	99,25	TK	257 543	-
15	100	724145,12	1028370,65	172,5	100		257 447	500
16	102,94	724147,42	1028372,48	172,52	102,94		257 072	500
17	106,63	724150,29	1028374,8	172,55	106,63	KT	256 602	500
18	107,12	724150,67	1028375,11	172,55	107,12	KZ	256 602	-
19	120	724160,68	1028383,22	172,65	120		256 602	-
20	134,55	724171,98	1028392,39	172,77	134,55	ZZ	256 602	-
21	137,93	724174,6	1028394,52	172,79	137,93	TK	256 602	-
22	140	724176,2	1028395,83	172,8	140		256,47	1000
23	147,46	724181,97	1028400,56	172,84	147,46		255 995	1000
24	155,15	724187,88	1028405,48	172,85	155,15	V	255 506	1000
25	157	724189,29	1028406,68	172,86	157	KT	255 388	1000
26	157,77	724189,88	1028407,17	172,86	157,77	Spád 0% (nejvyšší)	255 388	-
27	160	724191,58	1028408,61	172,85	160		255 388	-
28	175,75	724203,62	1028418,77	172,8	175,75	KZ	255 388	-
29	180	724206,87	1028421,51	172,78	180		255 388	-
30	189,72	724214,3	1028427,77	172,72	189,72	ZZ	255 388	-
31	198,71	724221,17	1028433,57	172,69	198,71	Spád 0% (nejnižší)	255 388	-
32	199,5	724221,78	1028434,08	172,69	199,5	TK	255 388	-
33	200	724222,16	1028434,4	172,69	200		255 433	700
34	200,17	724222,29	1028434,51	172,69	200,17	V	255 449	700
35	209,35	724229,35	1028440,38	172,73	209,35		256 284	700
36	210,62	724230,33	1028441,18	172,74	210,62	KZ	256 399	700
37	219,2	724237,01	1028446,57	172,81	219,2	KT	257,18	700
38	220	724237,64	1028447,07	172,81	220		257,18	-
39	225,78	724242,15	1028450,67	172,86	225,78	ZZ	257,18	-
40	234,76	724249,18	1028456,27	172,92	234,76	TK	257,18	-
41	240	724253,25	1028459,56	172,94	240		256 068	300
42	240,09	724253,32	1028459,62	172,94	240,09		256 049	300
43	245,19	724257,22	1028462,9	172,95	245,19	V	254 968	300
44	245,42	724257,4	1028463,05	172,95	245,42	KT	254 917	300

45	249,6	724260,57	1028465,77	172,95	249,6	Spád 0% (nejvyšší)	254 917	-
46	260	724268,47	1028472,53	172,94	260		254 917	-
47	264,6	724271,97	1028475,52	172,92	264,6	KZ	254 917	-
48	280	724283,67	1028485,54	172,84	280		254 917	-
49	300	724298,86	1028498,55	172,74	300		254 917	-
50	300,64	724299,34	1028498,97	172,74	300,64	ZZ	254 917	-
51	307,65	724304,67	1028503,53	172,71	307,65	TK	254 917	-
52	320	724314,06	1028511,55	172,68	320		255 075	5000
53	325,64	724318,35	1028515,2	172,67	325,64	Spád 0% (nejnižší)	255 147	5000
54	326,18	724318,76	1028515,55	172,67	326,18	V	255 153	5000
55	340	724329,31	1028524,49	172,69	340		255 329	5000
56	341,97	724330,81	1028525,76	172,7	341,97		255 354	5000
57	351,72	724338,26	1028532,04	172,74	351,72	KZ	255 479	5000
58	360	724344,61	1028537,37	172,78	360		255 584	5000
59	376,28	724357,1	1028547,81	172,87	376,28	KT	255 791	5000
60	380	724359,96	1028550,19	172,89	380		255 791	-
61	400	724375,33	1028562,99	172,99	400		255 791	-
62	402,35	724377,13	1028564,49	173,01	402,35	ZZ	255 791	-
63	412,78	724385,15	1028571,17	173,03	412,78	Spád 0% (nejvyšší)	255 791	-
64	420	724390,7	1028575,79	173,02	420		255 791	-
65	422,64	724392,72	1028577,48	173,01	422,64	V	255 791	-
66	428,72	724397,4	1028581,37	172,97	428,72	TK	255 791	-
67	434,68	724402,06	1028585,08	172,91	434,68		258 502	140
68	440	724406,35	1028588,23	172,85	440		260 921	140
69	440,64	724406,87	1028588,6	172,84	440,64	KT	261 212	140
70	442,93	724408,75	1028589,91	172,81	442,93	KZ	261 212	-
71	451,02	724415,38	1028594,53	172,68	451,02	KU, V	261 212	-